

31 Mar 69

Commanding Officer  
70th Engr Bn (Cbt)(A)  
ATTN: S-3  
APO 96297

Commanding Officer  
Co A, 70th Engr Bn  
APO 96297

### 1. Machinegun Mounts:

M-60 machineguns can be mounted at the gun ports of 20'x30' living/fighting bunkers by using a 2" pipe fastened to the floor and wall by metal brackets. A 2½" pipe can be substituted for the wittle by using an acetylene torch to cut the pipe into a "U" shaped configuration at one end. The machinegun can be belted to the 2½" pipe which can then be fitted directly over the 2" pipe allowing the machinegun to pivot freely.

### 2. Improvised Slings:

When no regular slings are available for lifting and moving small structures such as square bunkers, a temporary sling can be made using chains and 3"x8" lumber. Four (4) 3"x8" need to be notched at each end as spacers and two (2) 3"x8" need to be notched as supports for the bottom of the structure. This sling when used with a crane will allow rapid deployment with minimum damage to the structure.

Incl 1

### 3. Claymore Wires:

When using claymore wires for expedient electrical blasting, it is best to cut off the aluminum clamps which come attached to the wire. The end can then be restripped and tased directly to the wires leading out from the electrical blasting cap. This precaution is suggested because many times these aluminum clamps tend to short out your wires and cause a misfire.

*Andrew J. Lavins*  
ANDREW J LAVINS  
CPT, CR  
Commanding